



FDX XTREME

PREMIUM



TW Premium



TW 500 Premium

On request
hose reel kit

*Su richiesta kit
avvolgitubo*



NEW

**B&S
VANGUARD
ENGINES**
(18 or 31 HP)



RPM
deceleration kit

*Kit
deceleratore di
giri motore*

Rear wheel
with brake

*Ruota
posteriore
dotata di
freno*



FOR MORE INFO:
MAGGIORI INFORMAZIONI:



GENERAL FEATURES · CARATTERISTICHE GENERALI

- ø300mm 4 wheels with foamed-acting pneumatic
- Engines: Honda GX 690 or B&S Vanguard (18 or 31 HP)
- Gearbox (with 1560 rpm pump)
- Electrical starting
- No engine-oil safety device (oil-alert)
- Hours meter (on models with HONDA engine)
- Automatic decelerator to reduce the number of revs in the bypass phase
- Stainless steel gradual pressure restoration valve with EASY START
- Thermostatic valve
- Big water filter at pump inlet, readily serviceable cartridge type
- Water suction from external tank option (self-priming pumps)
- Suitable for high professional use
- 4 ruote schiumate ø300mm con effetto pneumatico
- Motori: Honda GX 690 oppure B&S Vanguard (18 o 31 HP)
- Riduttore di giri (con pompa a 1560 rpm)
- Avviamento elettrico
- Dispositivo di Sicurezza mancanza olio motore (oil-alert)
- Contatore (solo su modelli con motore HONDA)
- Deceleratore automatico per la riduzione del numero di giri in fase di by-pass
- Valvola a ripristino graduale della pressione in acciaio inox con EASY START
- Valvola termostatica
- Filtro acqua di grande dimensione in ingresso pompa a cartuccia ispezionabile
- Possibilità di aspirare acqua da serbatoio esterno (pompe autoadescenti)
- Uso altamente professionale

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

| CODE CODICE | MODELS MODELLI | PUMP POMPA | MAX | | WORK | | I/h | HP | kW | kg | (L x W x H) cm |
|----------------|--------------------------------------|----------------|-----|------|---------|-------|-----------|------|------|-----|----------------|
| | | | bar | MPa | bar | MPa | | | | | |
| 9058 0025 | FDX Xtreme 18/350 Vanguard B&S 18 HP | TW Premium | 360 | 36 | 50÷350 | 5÷35 | 410÷1080 | 18,0 | 13,4 | 150 | 100 x 82 x 85 |
| 9058 0001 | FDX Xtreme 15/500 Honda GX690 | TW Premium 500 | 520 | 52 | 100÷500 | 10÷50 | 440÷990 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0002 | FDX Xtreme 18/400 Honda GX690 | TW Premium 500 | 415 | 41,5 | 50÷400 | 5÷40 | 380÷1080 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0003 | FDX Xtreme 21/350 Honda GX690 | TW Premium | 360 | 36 | 50÷350 | 5÷35 | 480÷1260 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0004 | FDX Xtreme 30/280 Honda GX690 | TW Premium | 280 | 28 | 50÷270 | 5÷27 | 770÷1800 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0005 | FDX Xtreme 36/230 Honda GX690 | TW Premium | 230 | 23 | 30÷220 | 3÷22 | 800÷2160 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0006 | FDX Xtreme 42/180 Honda GX690 | TW Premium | 180 | 18 | 30÷170 | 3÷17 | 1060÷2520 | 22,0 | 16,4 | 150 | 100 x 82 x 85 |
| 9058 0024 | FDX Xtreme 21/500 Vanguard B&S 31 HP | TW Premium 500 | 520 | 52 | 100÷500 | 10÷50 | 560÷1260 | 31,0 | 23,1 | 150 | 100 x 82 x 85 |

STANDARD EQUIPMENT · DOTAZIONE STANDARD

| | | |
|---|---|---|
| <p>GH 401 gun with Swivel (n.2 o-ring) Pistola GH 401 con Swivel (n.2 o-ring)</p> | <p>L50 straight S.S. lance with ball quick coupler, without nozzles Lancia dritta L50 inox con attacco rapido a sfere, senza ugelli</p> | <p>25° spray nozzle, 1/4" MEG connection Ugello con getto a lama 25° attacco 1/4" MEG</p> |
| <p>GH 501 stainless steel spray gun with quick couplers Pistola GH 501 inox con attacchi rapidi</p> | <p>Straight stainless steel lance, with adjustable handle Lancia inox dritta, con impugnatura regolabile</p> | <p>Flat stainless-steel spray nozzle with ceramic insert Ugello inox getto piatto con inserto in ceramica</p> |
| <p>Rubber delivery hose kit Kit tubo gomma mandata 10 m</p> | <p>20 mt delivery hose kit with quick coupler M24x1,5 Kit tubo mandata 20 mt con attacchi rapidi M24x1,5</p> | <p>Self cleaning water filter Filtro acqua autopulente</p> |